

TECHNICAL INSTRUCTIONS

KANADIAN KEN'S SOLO RACK 1998-2001 5th GENERATION VFR

KIT CONTENTS

Quantity	Part Description
1	Solo Rack
2	M8 X 40mm Button Head Bolt
2	M8 X 50mm Button Head Bolt
4	M8 Washers
2	25mm Spacer
2	35mm Spacer

INSTRUCTIONS

NOTE: Canadian Ken's Solo Rack is designed to mount in place of the passenger grab handles. The rear passenger seat cowl cannot be used with the rack unless modified by cutting.

1. Remove rear seat cowl, seat, and passenger grab handles if any are currently on the motorcycle.



2. Install solo rack using the supplied hardware. The 35mm spacer should be used on the rear mounting holes along with the 50mm long bolts and washers.



25mm spacer
40mm bolt &
washer

35mm spacer
50mm bolt &
washer

NOTE: If needed, an 8mm flat washer can be inserted between the solo rack and spacer (either front or rear) to level the rack, depending on the stance of your individual motorcycle.

3. Torque bolts to 25 lb-ft (34 Nm).



4. The solo rack is pre-drilled with mounting holes for your trunk plate. Mount the plate and torque bolts per the mounting plate manufacturer's specs.
5. If the mounting plate bolts protrude through the bottom of the rack more than the thickness of the mounting plate nut, the bolt should be cut off even with the nut to assist with seat removal and installation.
6. Install the seat by inserting the passenger portion under the solo rack first, and then spread the front seat "wings" while lowering in place.