HONDA Come ride with us.

Colouring Concept

Introduced this year, the newest generation VFR returns to dominate the 750cc Super Sport class with its unrivalled combination of performance, precision technology, quality and comfort—features that have seen it consistently hailed as one of the finest motorcycles of the last decade. For 1999, the VFR strafes the highways in three exciting colour variations: A bright, aggressive solid red that has come to be identified as the VFR's signature colour; a sultry pearlescent black that reflects a rainbow of colours to emphasize the VFR's prestigious level of technological excellence; and a brilliant new pearlescent yellow being used for the first time ever to draw attention to the VFR's sporty nature.

Colours

- Italian Red
- Pearl Prism Black
- Pearl Shining Yellow

New Features

• New colour variations.



Specifications

Specifications

VFR (ED-type)

Engine		Liquid-cooled 4-stroke 16-valve DOHC 90° V-4
Bore × Stroke		72×48mm
Displacement		781.7cm ³
Compression Ratio		11.6 : 1
Carburettor		Electronic direct fuel injection
Max. Power Output		110PS/10,500rpm (DIN) (81kW/10,500min ⁻¹)
Max. Torque		8.4kg-m/8,500rpm (DIN) (82Nm/8,500min ⁻¹)
Ignition		Computer-controlled digital transistorized with electronic advance
Starter		Electric
Transmission		6-speed
Final Drive		'O'-ring sealed chain
Dimensions	(L×W×H)	$2,095 \times 735 \times 1,190$ mm
Wheelbase		1,440mm
Seat Height		805mm
Ground Clearance		130mm
Fuel Capacity		21 litres
Wheels	Front	17 imes MT3.50 'U'-section 6-spoke cast aluminium
	Rear	$17 \times MT5.50$ 'U'-section 5-spoke cast aluminium
Tyres	Front	120/70 ZR17 (58W)
	Rear	180/55 ZR17 (73W)
Suspension	Front	41mm H.M.A.S. cartridge-type telescopic fork with stepless
		preload adjustment, 109mm axle travel
	Rear	Pro-Link with 7-step preload and stepless rebound-adjustable
		gas-charged H.M.A.S. damper, 120mm axle travel
Brakes	Front	296 imes 4.5mm dual discs with Combined 3-piston calipers and
		sintered metal pads
	Rear	256×6 mm disc with Combined 3-piston caliper and sintered metal pads
Dry Weight		208kg

All specifications are provisional and subject to change without notice.

